

# *Toufic T. Berbari & Fils*

QUARTIER CHRIST ROI  
ZOUK MOUSBEH

LIBAN

TEL : 09 218271 - 09 218272  
FAX : +961 9 218272  
B .P. : 250 ZOUK MICKAEL

E- MAIL: [touficberbari@wise.net.lb](mailto:touficberbari@wise.net.lb)



## **NOULA 466 Quick Drying Wood Stain**

NOULA 466 provides decorative design and physical surface protection against damp and UV rays, as well as blocking fungal spores. By using NOULA 466 wood protection you obtain a finish that is free from, or low in active substances.

### **Important tasks:**

- Remove impurities using an appropriate method, e.g. a scraper or wooden brush
- Use a scraper to remove hard spots (hardened areas); remove resin specks with cellulose thinners.
- Sand with grit 60-80 sandpaper (coarse), 100-120 (medium), 180-220 (fine), steel wool (coarse and fine, non-rusting) and a scouring pad (fine).
- Always remove sanding residue with a painter's duster.
- A sanding block makes sandpaper easier to control. For larger areas, hand-held sanders are recommended.

### **For all woods maintenance used externally:**

- Enhances the wood with a translucent, silky finish.

- **Water repellent • UV-protective**

- Provides an effective protection against the development of insects, mould and blue stain
- Ideal for facades, cladding, doors, windows, shutters, eaves and all types of outdoor wood
- No flaking - no blistering

To achieve the best effect when applying a coat, the surface must be dry, clean and free of dust, grease, oil, wax and salt. Typical contaminants such as algae, mould growth, bird droppings, cobwebs, etc. must be completely removed.

### **Disclaimer**

It is the user responsibility to get sure of the use of the product in a correct way and place. As Noula paints has no control over the improper usage of the product we cannot be hold responsible for any consequences associated with their use.