

Toufic T. Berbari & Fils

QUARTIER CHRIST ROI
ZOUK MOUSBEH
LIBAN

TEL : 09 218271 - 09 218272
FAX : 00961 9 218272
B.P. : 250 ZOUK MICKAEL
E- MAIL: info@noula.com.lb



800 HI-TEX

Product description

NOULA HI-TEX paint is based on a high-quality co-polymer acrylic emulsion providing a very good adhesion on different kinds of surfaces.

Recommended use

NOULA HI-TEX is ideal for interior walls where very good washability is required. It has a very high scrub resistance, very good levelling and excellent hiding power.

Surface preparation

Surface to cover must be solid, clean and dry free from oil and grease.

And it must be free from any growth or contamination.

On unpainted plaster, cement walls or other new surfaces or on old surfaces from which paint, use our pigmented sealer or undercoat.

Properties

PVC: 55%

Density: 1.42

Application

Solvent: must be thinned with clean water.

Dilution: 30% to 40% with water

Application temperature: between +5 and +40 Celsius

Application tools: can be applied by brush, roller or airless spray machine.

Shelf life: 24 months

Spreading rate

Covering: 15m²/l

Opacity: 11m²/l

Contrast ratio: $(R_b/R_w \times 100) = 96.2\%$

Drying time

Substrate temperature	10oC	25oC	40oC	
Touch dry	4	2	1	H
Dry to cover coat	12	6	3	H
Ready to stress	96	48	24	H

Storage and handling

Keep out of reach of children.

Avoid contact with eyes.

24 months stored in warehouse below 35oC in original unopened packs.

Disclaimer

It is the user responsibility to get sure of the use of the product in a correct way and place.

As Noula paints has no control over the improper usage of the product we cannot be hold responsible for any consequences associated with their use.