

Toufic T. Berbari & Fils

QUARTIER CHRIST ROI
ZOUK MOUSBEH
LIBAN

TEL : 09 218271 - 09 218272
FAX : 00961 9 218272
B.P. : 250 ZOUK MICKAEL
E- MAIL: info@noula.com.lb



1920 INN-TEX

Product description

NOULA INN-TEX paint is based on a high-quality co-polymer acrylic emulsion providing a very good adhesion on different kinds of surfaces.

NOULA INN-TEX is a textured coating giving fine to coarse texture depending on the dilution.

Recommended use

NOULA INN-TEX is ideal for interior walls it the best effective price/quality ratio solution.

Surface preparation

Surface to cover must be solid, clean and dry free from oil and grease.

And it must be free from any growth or contamination.

On unpainted plaster, cement walls or other new surfaces or on old surfaces from which old paint has been removed,

use **NOULA INN-TEX** itself as primer.

When used to prime INN-TEX should be diluted up to 40%

Properties

Dry content: 82%

Density: 1.83

Application

Solvent: must be thinned with clean water.

Dilution: 0% to 10% with water

Application temperature: between +5 and +40 Celsius

Application tools: by roller

Shelf life: 24 months

Spreading rate

Covering: 1,5 to 2 kg / m²

Storage and handling

Keep out of reach of children.

Avoid contact with eyes.

24 months stored in warehouse below 35°C in original unopened packs.

Disclaimer

It is the user responsibility to get sure of the use of the product in a correct way and place.

As Noula paints has no control over the improper usage of the product we cannot be hold responsible for any consequences associated with their use.